

breathing apparatus complying with the requirements of §1910.134 of this chapter shall be available in a suitably labeled cabinet for immediate use in case of emergency caused by oxygen deficiency or hydrogen sulfide. Any employee entering a tank in an emergency shall, in addition to respiratory protective equipment, wear a lifeline and safety harness to facilitate rescue. At least two other employees, similarly equipped, shall be continuously stationed outside the tank to observe and to provide rescue services.

(d) The plant superintendent and foremen shall be trained and knowledgeable about the hazards of hydrogen sulfide and oxygen deficiency. They shall be trained in the use of appropriate respiratory and other protective equipment, and in rescue procedures. Other supervisory plant personnel shall be informed of these hazards and instructed in the necessary safety measures, including use of respiratory and rescue equipment.

(e) Supervisory personnel shall be on hand at dockside to supervise discharging of baidwater from vessels.

[48 FR 30909, July 5, 1983, as amended at 65 FR 40940, June 30, 2000]

Subpart E—Personal Protection

§ 1917.91 Eye and face protection.

(a)(1) The employer shall ensure that each affected employee uses appropriate eye and/or face protection where there are exposures to eye and/or face hazards. Such equipment shall comply with American National Standards Institute, ANSI Z-87.1-1989, "Practice for Occupational and Educational Eye and Face Protection."

(2) For employees wearing corrective spectacles, eye protection equipment required by paragraph (a)(1) of this section must be of a type which can be worn over spectacles. Prescription ground safety lenses may be substituted if they provide equivalent protection.

(3) For additional requirements covering eye protection against radiant energy, see §1917.152(h).

(b) Eye protection equipment shall be maintained in good condition.

(c) Used eye protection equipment shall be cleaned and disinfected before reissuance to another employee.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40201, July 25, 1997]

§ 1917.92 Respiratory protection.

(See §1917.1(a)(2)(x)).

[65 FR 40941, June 30, 2000]

§ 1917.93 Head protection.

(a) The employer shall ensure that each affected employee wears a protective helmet when working in areas where there is a potential for injury to the head from falling objects.

(b) Such equipment shall comply with American National Standards Institute, ANSI Z-89.1-1986, "Personnel Protection-Protective Headwear for Industrial Workers-Requirements."

(c) Protective hats previously worn shall be cleaned and disinfected before issuance by the employer to another employee.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40201, July 25, 1997]

§ 1917.94 Foot protection.

(a) The employer shall ensure that each affected employee wears protective footwear when working in areas where there is a danger of foot injuries due to falling or rolling objects or objects piercing the sole.

(b) Such equipment shall comply with American National Standards

Institute, ANSI Z-41-1991, "American National Standard for Personal Protection-Protective Footwear."

[62 FR 40201, July 25, 1997]

§ 1917.95 Other protective measures.

(a) *Protective clothing.* (1) Employees performing work that requires special protective clothing shall be directed by the employer to wear the necessary special protective clothing.

(2) When necessary, protective clothing previously worn shall be cleaned and disinfected before reissuance.

(b) *Personal flotation devices (PFDs).* (1) The employer shall provide, and shall direct the wearing of PFDs for those employees, such as line handlers, who are engaged in work in which they may be pulled into the water: